

Scientific Documentation

MI501, Light Mineral Oil, NF

Not appropriate for regulatory submission. Please visit www.spectrumchemical.com or contact Tech Services for the most up-to-date information contained in this information package.

Spectrum Chemical Mfg Corp

769 Jersey Avenue New Brunswick, NJ 08901 Phone 732.214.1300



Dear Customer,

Thank you for your interest in Spectrum's quality products and services.

Spectrum has been proudly serving our scientific community for over 45 years. It is our mission to manufacture and distribute fine chemicals and laboratory products with Quality and delivery you can count on every time.

To accomplish our mission, Spectrum utilizes our sourcing leverage and supplier qualification expertise in offering one of the industry's most comprehensive line of fine chemical products under one brand, in packaging configurations designed to meet your research and production requirements. Our product grades include: USP, NF, BP, EP, JP, FCC, ACS, KSA, Reagent grade, as well as DEA controlled substances. We operate facilities in the United States on the East Coast, West Coast, as well as in Shanghai, China in order to provide the best logistical support for our customers.

At Spectrum, Quality is priority number one. Suppliers with the best qualifications are preferred and we employ full-functioning in-house analytical laboratories at each of our facilities. Our facilities and systems are USFDA registered and ISO certified. We frequently host customer audits and cherish opportunities for improvements. Quality is engrained into our culture. Quality is priority number one.

In the following pages, we have designed and prepared documented scientific information to aid you in your initial qualification or your continual use of our products. Please do not hesitate to contact us if further information or the most up-to-date documentation is desired from any of the covered areas.

We appreciate your business and we look forward to hearing from you.

Sincerely,

Alan Wang, MSQA, ASQ CQA Senior Manager of Technical Services techservices@spectrumchemical.com

Table of Contents

- Product Specification
- Safety Data Sheet (SDS)
- Manufacturer
- Certification of Quality Mangement System (QMS)
- Certification of current Good Manufacturing Practices (cGMP)
- Product BSE/TSE Statement
- Product Allergen Statement
- Product Aflatoxin Statement
- General Label Information Sample Label
- Product Certificate of Analysis Sample(s)
- General Lot Numbering System Guidance
- Stability Shelf Life Guidance



Specification for Light Mineral Oil, NF (MI501)

Item Number	<u>MI501</u>
Item	Light Mineral Oil, NF
CAS Number	8042-47-5
Molecular Formula	
Molecular Weight	
MDL Number	
Synonyms	Liquid Paraffin ; Liquid Petrolatum

Test	Specification		
	Min	Max	
SPECIFIC GRAVITY @ 25°C	0.818 - 0.880		
VISCOSITY @40.0 C	3.0- 34.4 mm²/s		
ACIDITY	TO PASS TEST		
READILY CARBONIZABLE SUBSTANCES	TO PASS TEST		
POLYCYCLIC AROMATIC HYDROCARBONS	TO PASS TEST		
SOLID PARAFFIN	TO PASS TEST		
IDENTIFICATION	TO PASS TEST		
RESIDUAL SOLVENTS	TO PASS TEST		
SULFUR COMPOUNDS	TO PASS TEST		
EXPIRATION DATE			

Spectrum Chemical Mfg Corp

Corporate Headquarters: 769 Jersey Ave. New Brunswick, NJ 08901 732.214.1300

14422 S. San Pedro St. Gardena, CA 90248 310.516.8000

West Coast Facility:





SAFETY DATA SHEET

Preparation Date: 12/16/2015	Revision Date: 12/16/2015	Revision Number: G1

1. IDENTIFICATION

Product identifier

Product code: MI501

Product Name: LIGHT MINERAL OIL, NF

Other means of identification

Synonyms: No information available

CAS #: 8042-47-5
RTECS # PY8047000
CI#: Not available

Recommended use of the chemical and restrictions on use

Recommended use: Lubricant. Medication.
Uses advised against No information available

Supplier: Spectrum Chemical Mfg. Corp

14422 South San Pedro St.

Gardena, CA 90248 (310) 516-8000

Order Online At: https://www.spectrumchemical.com

Emergency telephone numberChemtrec 1-800-424-9300Contact Person:Martin LaBenz (West Coast)Contact Person:Ibad Tirmiz (East Coast)

2. HAZARDS IDENTIFICATION

Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a dangerous substance or mixture according to the Globally Harmonized System (GHS)

Label elements

Not classified	_

Hazards not otherwise classified (HNOC)

Not Applicable

Other hazards Not available

Product code: MI501 Product name: LIGHT MINERAL OIL, 1/11

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %	Trade Secret
Light Mineral Oil	8042-47-5	100	*
8042-47-5			

4. FIRST AID MEASURES

First aid measures

General Advice: Poison information centers in each State capital city can provide additional

assistance for scheduled poisons (13 1126)

Skin Contact: Wash off immediately with soap and plenty of water removing all contaminated clothes and

shoes. Get medical attention if irritation develops. Consult a physician if necessary.

Eye Contact: Flush eyes with water for 15 minutes. Get medical attention if irritation occurs. If symptoms

persist, call a physician.

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

Get medical attention.

Ingestion: Do not induce vomiting without medical advice. Never give anything by mouth to an

unconscious person. Consult a physician if necessary.

Most important symptoms and effects, both acute and delayed

Symptoms May cause eye irritation. May cause skin irritation. Thirst. May cause diarrhea. Vomiting. May

cause abdominal discomfort.

Indication of any immediate medical attention and special treatment needed

Notes to Physician: Treat symptomatically

Protection of first-aiders

First-Aid Providers: Avoid exposure to blood or body fluids. Wear gloves and other necessary protective clothing. Dispose of contaminated clothing and equipment as bio-hazardous waste

5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Carbon dioxide (CO2). Dry chemical. Foam.

Unsuitable Extinguishing Media: Do not use a solid (straight) water stream as it may scatter

and spread fire.

Specific hazards arising from the chemical

Hazardous Combustion Products: Carbon monoxide; Carbon dioxide

Specific hazards: May be combustible at high temperatures

Special Protective Actions for Firefighters

Product code: MI501 Product name: LIGHT MINERAL OIL, 2/11

Specific Methods: For large fires, flood fire area with water from a distance. For

larger fires, use water spray or fog. Cool containers with flooding quantities of water until well after fire is out.

Special Protective Equipment for Firefighters:

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent)

and full protective gear

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions: Ensure adequate ventilation. Use personal protective equipment. Avoid contact with skin, eyes

and clothing. Remove all sources of ignition.

Environmental precautions Prevent further leakage or spillage if safe to do so.

Methods and material for containment and cleaning up

Methods for containmentStop leak if you can do it without risk. Absorb spill with inert material (e.g. vermiculite,

dry sand or earth).

Methods for cleaning upAbsorb spill with inert material (e.g. vermiculite, dry sand or earth), then place in a

suitable chemical waste container. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Precautions for safe handling

Technical Measures/Precautions:

Provide sufficient air exchange and/or exhaust in work rooms. All equipment used when handling the product must be grounded. Remove all sources of ignition. Keep away from incompatible materials.

Safe Handling Advice

Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Do not breathe vapors or spray mist. Do not ingest. Do not smoke. Keep away from open flames, hot surfaces and sources of ignition. Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

Technical Measures/Storage Conditions:

Keep container tightly closed in a dry and well-ventilated place. Store at room temperature in the original container. Store away from incompatible materials. Protect from light. Sensitive to light. Store in light-resistant containers. Store under nitrogen.

Incompatible Materials:

Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

National occupational exposure limits

United States

Components	OSHA	NIOSH	ACGIH	AIHA WHEEL
Light Mineral Oil	None	None	None	None
8042-47-5				

Canada

Product code: MI501 Product name: LIGHT MINERAL OIL, 3 / 11

Components	Alberta	British Columbia	Ontario	Quebec
Light Mineral Oil	None	None	None	None
8042-47-5				

Australia and Mexico

Components	Australia	Mexico
Light Mineral Oil	None	None
8042-47-5		

Appropriate engineering controls

Engineering measures to reduce exposure: Ensure adequate ventilation. Provide exhaust ventilation or

other engineering controls to keep the airborne

concentrations of vapors and mist below their respective

threshold limit value.

Individual protection measures, such as personal protective equipment

Personal Protective Equipment

Eye protection: Goggles.

Skin and body protection: Chemical resistant apron. Long sleeved clothing. Gloves.

Respiratory protection: Respiratory protection is not necessary for normal handling. Good room ventilation

or use of local exhaust (fume hood) is sufficient. Use a vapor respirator under conditions where exposure to the substance is apparent (e.g. generation of high concentrations of mist or vapor, inadequate ventilation, development of respiratory tract irritation), and engineering controls are not feasible. Be sure to use an

approved/certified respirator or equivalent. .

Hygiene measures: Avoid contact with skin, eyes and clothing. When using, do not eat, drink or smoke.

Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Product code: MI501 Product name: LIGHT MINERAL OIL, 4/11

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Appearance: Color:

Liquid Oily. Viscous. Water-white. Colorless.

Odor: Taste Formula:

Odorless. No information available No information available

Molecular/Formula weight: Flammability: Flash point (°C):

No information available No information available 93.3

Flashpoint (°C/°F): Flash Point Tested according to: Autoignition Temperature (°C/°F):

93.3 °C/200 °F Not available

Lower Explosion Limit (%): Upper Explosion Limit (%): pH:

No information available No information available No information available

Melting point/range(°C/°F): Boiling point/range(°C/°F): Decomposition temperature(°C/°F):

No information available >230°C/446°F

218-643 °C/424.4-1189 °F

Bulk density: Density (g/cm3): Specific gravity:

No information available No information available 0.818-0.880

Vapor pressure @ 20°C (kPa): Evaporation rate: Vapor density:

<0.1 No information available No information available

VOC content (g/L):Odor threshold (ppm):Partition coefficientNo information availableNo information available(n-octanol/water):

Viscosity: Miscibility: Solubility:

3.0-34.4 mm2/s @ 40 deg. C No information available Soluble in most organic solvents

Insoluble in water

>6

No information available

No information available

10. STABILITY AND REACTIVITY

Reactivity

Reactive with strong oxidizing agents

Chemical stability

Stability: Stable under recommended storage conditions

Possibility of Hazardous Reactions: Hazardous polymerization does not occur

Conditions to avoid: Heat. Ignition sources. Incompatible materials. Exposure to light.

Incompatible Materials: Strong oxidizing agents.

Hazardous decomposition products: Carbon oxides.

Other Information

Corrosivity: No information available

Special Remarks on Corrosivity: No information available

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product code: MI501 Product name: LIGHT MINERAL OIL, 5 / 11

Principal Routes of Exposure:

Skin. Ingestion.

Acute Toxicity

Component Information

Light Mineral Oil - 8042-47-5

LD50/oral/rat = >5000 mg/kg

LD50/oral/mouse = No information available

LD50/dermal/rat = No information available

LD50/dermal/rabbit = No information available

LC50/inhalation/rat = No information available

LC50/inhalation/mouse = No infomation available

Other LD50 or LC50information = No information available

Product Information

LD50/oral/rat =

VALUE- Acute Tox Oral = >5000mg/kg

LD50/oral/mouse =

Value - Acute Tox Oral = No information available

LD50/dermal/rabbit

VALUE-Acute Tox Dermal = No information available

LD50/dermal/rat

VALUE -Acute Tox Dermal = No information available

LC50/inhalation/rat

VALUE-Vapor = No information available

VALUE-Gas = No information available

VALUE-Dust/Mist = No information available

LC50/Inhalation/mouse

VALUE-Vapor = No information available

VALUE - Gas = No information available

VALUE - Dust/Mist = No information available

Symptoms

Skin Contact: May cause skin irritation. Although this material is not known to be an irritant, it may

be midly irritating in sensitive individuals.

Eye Contact: May cause eye irritation. May cause slight temporary eye irritation.

Inhalation Not expected to be an inhalation hazard. May cause respiratory tract irritation.

Symptoms may include coughing and shortness of breath. It is not expected to be an inhalalation hazard during usual industrial handling and at ambient conditions unless it is misted or aerosolized. Caution should be taken to prevent aerosolization or misting. If aspiration occurs upon inhalation of mist or aerosol, it may lead to chemical or lipoid pneumonitis, aspiration or lipoid pneumonia, and pulmonary

edema.

Product code: MI501 Product name: LIGHT MINERAL OIL, 6 / 11

Ingestion Regarded as essentially non-toxic. May cause abdominal discomfort. May cause

stomach cramping. It can have a purging or laxative effect.. May cause vomiting. May

cause diarrhea. May cause thirst.

Aspiration hazard No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Chronic Toxicity Prolonged or repeated ingestion may affect the liver

Prolonged or repeated ingestion may cause loss of appetite

Regular ingestion of mineral oil during pregnancy may reduce absorption of Vitamin

K and produce hypoprothrombinemia in the newborn

Heavy exposure to oil mist in the absence of adequate ventilation may cause lipoid

pneumopnia. It may also cause slight basal lung fibrosis

Sensitization: No information available

Mutagenic Effects: No information available

Carcinogenic effects: Not considered carcinogenic

Components	IARC	ACGIH -	NTP	OSHA HCS -	Australia - Notifiable	Australia - Prohibited
-		Carcinogens		Carcinogens	Carcinogenic	Carcinogenic
				_	Substances	Substances
Light Mineral Oil	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed

Reproductive toxicity

No data is available

Reproductive Effects:

Developmental Effects:

Teratogenic Effects:

No information available
No information available
No information available

Specific Target Organ Toxicity

STOT - single exposure
STOT - repeated exposure
Target Organs:

No information available
No information available

12. ECOLOGICAL INFORMATION

Ecotoxicity

Ecotoxicity effects: Aquatic environment.

Persistence and degradability: No information available

Bioaccumulative potential: No information available

Mobility: No information available

13. DISPOSAL CONSIDERATIONS

Product code: MI501 Product name: LIGHT MINERAL OIL, 7 / 11

13. DISPOSAL CONSIDERATIONS

Disposal Methods

Waste from residues / unused products:

Waste must be disposed of in accordance with Federal, State and Local regulation.

Contaminated packaging:

Empty containers should be taken for local recycling, recovery or waste disposal Do not re-use empty containers Dispose of as unused product.

Components	RCRA - F Series Wastes	RCRA - K Series Wastes	RCRA - P Series Wastes	RCRA - U Series Wastes
Light Mineral Oil	None	None	None	None

14. TRANSPORT INFORMATION

DOT

UN-No: Not Regulated

Proper Shipping Name:
Hazard Class:
Subsidiary Risk:
No information available
No information available
No information available

Packing Group: None

ERG No: No information available

Marine Pollutant No data available DOT RQ (lbs): No information available

TDG (Canada)

UN-No: Not Regulated

Proper Shipping Name:
Hazard Class:
Subsidiary Risk:
Packing Group:
No information available

ADR

UN-No: Not Regulated

Proper Shipping Name:
Hazard Class:
Packing Group:
Subsidiary Risk:
Classification Code:
Description:
No information available

IMO / IMDG

UN-No: Not Regulated

Proper Shipping Name: No information available **Hazard Class:** No information available **Subsidiary Risk:** No information available **Packing Group:** No information available **Description:** No information available IMDG Page: No information available Marine Pollutant No information available MFAG: No information available No information available **Maximum Quantity:**

Product code: MI501 Product name: LIGHT MINERAL OIL, 8 / 11

14. TRANSPORT INFORMATION

RID

UN-No: Not Regulated

Proper Shipping Name:
Hazard Class:
Subsidiary Risk:
Packing Group:
Classification Code:
Description:
No information available

ICAO

UN-No: Not Regulated

Proper Shipping Name:
Hazard Class:
Subsidiary Risk:
Packing Group:
No information available

IATA

UN-No: Not Regulated

Proper Shipping Name:
Hazard Class:
Subsidiary Risk:
Packing Group:
No information available

15. REGULATORY INFORMATION

International Inventories

Components	U.S. TSCA	KOREA KECL		Japan ENCS	CHINA	Australia	EINECS-No.
			(PICCS)			(AICS)	
Light Mineral Oil	Not Listed	Not present					

U.S. Regulations

California Prop. 65: Safe Drinking Water and Toxic Enforcement Act of 1986.

Chemicals Known to the State of California to Cause Cancer:

This product does not contain a chemical requiring a warning under California Prop. 65. (See table below)

Chemicals Known to the State of California to Cause Reproductive Toxicity:

This product does not contain a chemical requiring a warning under California Prop. 65. (See table below)

Components	Carcinogen	Developmental Toxicity		Female Reproductive Toxicity:
Light Mineral Oil	Not Listed	Not Listed	Not Listed	Not Listed

CERCLA/SARA

Components	CERCLA - Hazardous	Section 302 Extremely	Section 302 Extremely	Section 313 -	Section 313 - Reporting
	Substances and their	Hazardous	Hazardous	Chemical Category	de minimis
	Reportable Quantities	Substances and TPQs	Substances and RQs		
Light Mineral Oil	None	None	None	None	None

Product code: MI501 Product name: LIGHT MINERAL OIL, 9 / 11

U.S. TSCA

•	TSCA Section 5(a)2 - Chemicals With Significant New Use Rules (SNURS)	TSCA 8(d) -Health and Safety Reporting
Light Mineral Oil	Not Applicable	Not Applicable

Canada

WHMIS hazard class:

Non-controlled

Canada Controlled Products Regulation:

This product has been classified according to the hazard criteria of the CPR (Controlled Products Regulation) and the MSDS contains all of the information required by the CPR.

Inventory

Components	Canada (DSL)	Canada (NDSL)
Light Mineral Oil	Not Listed	Not Listed

Components	CEPA Schedule I - Toxic Substances	CEPA - 2010 Greenhouse Gases Subject to Manditory
		Reporting
Light Mineral Oil	Not listed	Not listed

EU Classification

R-phrase(s)

not determined (not applicable)

S -phrase(s)

none

Components	Classification	Concentration Limits:	Safety Phrases
Light Mineral Oil		No information	

The product is classified in accordance with Annex VI to Directive 67/548/EEC

Indication of danger:

None.

Product code: MI501 Product name: LIGHT MINERAL OIL, 10 / 11

16. OTHER INFORMATION

Preparation Date:12/16/2015Revision Date:12/16/2015Prepared by:Sonia Owen

Disclaimer:

All chemicals may pose unknown hazards and should be used with caution. This Safety Data Sheet (SDS) applies only to the material as packaged. If this product is combined with other materials, deteriorates, or becomes contaminated, it may pose hazards not mentioned in this SDS. The physical properties reported in this SDS are obtained from the literature and do not constitute product specifications. Information contained herein does not constitute a warranty, whether expressed or implied, as to the safety, merchantability or fitness of the goods for a particular purpose. Spectrum Chemicals & Laboratory Products, Inc. assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied. It shall be the user's responsibility to develop proper methods of handling and personal protection based on the actual conditions of use. While this SDS is based on technical data judged to be reliable, Spectrum assumes no responsibility for the completeness or accuracy of the information contained herein.

End of Safety Data Sheet

Product code: MI501 Product name: LIGHT MINERAL OIL. 11 / 11



Manufacturer

Product Covered: MI501, Light Mineral Oil, NF

Spectrum takes ownership as the manufacturer for the Spectrum product listed above and provides full quality assurance, customer service, and technical product support.

While information concerning the raw material manufacturer of our starting materials is considered proprietary, such information can be made available upon request contingent on demonstration of business volume justification and successful execution of confidential disclosure agreement (CDA).

Requests for disclosure of proprietary raw material manufacturer information may be submitted to the assigned account representative for consideration.

Sincerely,

Alan Wang, MSQA, ASQ CQA Senior Manager of Technical Services techservices@spectrumchemical.com

Certificate of Registration



This is to certify that the quality management system of

Spectrum Chemicals and Laboratory Products, Lac

Main Site: 14422 South San Pedro Street, Gardena, California, 90248, USA

Additional Sites: 13915 South Main Street, Los Angeles, California, 90061, USA 755 Jersey Avenue, New Brunswick, New Jersey, 08901, USA 769 Jersey Avenue, New Brunswick, New Jersey, 08901, USA 7400 North Oracle Road, Suite 221, Tucson, Arizona, 85704, USA

has been assessed and registered by Intertek as conforming to the requirements of

ISO 9001:2008

The quality management system is applicable to

California and New Jersey sites: The manufacture and distribution of specialty fine chemicals, solutions, equipment, supplies and products for the laboratory, pharmaceutical, food, healthcare, cosmetic, fragrance, biotechnology, environmental and process industries.

Arizona site: Supporting Spectrum's two manufacturing facilitates by: selecting and qualifying distributors of Laboratory and Safety Equipment; processing bids and quotes to generate new sales opportunities; sourcing bulk chemicals in support of bulk bids and quotes; assisting production operations through order expediting and IT infrastructure support.

Certificate Number: 94-316m-01

Initial Certification Date: 27 December 1994 Certificate Issue Date: 29 January 2016 Certificate Expiry Date: 14 September 2018

Calin Moldovean, President Intertek Testing Services NA, Inc. 900 Chelmsford Street, Suite 301-3, Lowell, MA, USA ARAB
ACCREDITED
ISO/IEC17021
MANAGEMENT SYSTEMS
CERTIFICATION BODY



In the issuance of this certificate, Intertek assumes no liability to any party other than to the Client, and then only in accordance with the agreed upon Certification Agreement. This certificate's validity is subject to the organization maintaining their system in accordance with Intertek's requirements for systems certification. Validity may be confirmed via email at certificate.validation@intertek.com or by scanning the code to the right with a smartphone.

Certificate of Registration



This is to certify that the quality management system of

Spectrum China Ltd.

Building A20, No. 3802, Shengang Road, Songjiang District, Shanghai, China

has been assessed and registered by Intertek as conforming to the requirements of

ISO 9001: 2008

The quality management system is applicable to:

Provision of service of purchase, testing and sales for chemical products, repacking of non-hazardous chemical products.

Organization Code: 77762704-8
Certificate Number: 111310001-01
Certificate Issue Date: 17 November 2015
Certificate Expiry Date: 14 September 2018







Authorised Signature: Calin Moldovean – President, Business Assurance Intertek Certification Limited, 10A Victory Park, Victory Road, Derby DE24 8ZF, United Kingdom Intertek Certification Limited is a UKAS accredited body under schedule of accreditation no. 014.

In the issuance of this certificate, Intertek assumes no liability to any party other than to the client, and then only in accordance with the agreed upon Certification Agreement. This certificate's validity is subject to the organization maintaining their system in accordance with Intertek's requirements for systems certification. Validity may be confirmed via email at certificate.com or by scanning the code to the right with a smartphone.

The annual validity of the certificate can also be checked through the website http://www.cnca.gov.cn of CNCA in China.





March 28, 2016

Certificate of cGMP

Dear Valued Customer:

Spectrum Chemicals and Laboratory Products certify that our USP, NF, FCC, EP, BP, JP, and food grade products are produced, processed, packaged and held in compliance with current Good Manufacturing Practices (cGMP) in accordance with the applicable parts of 21 CFR, parts 210 and 211 of the Code of Federal Regulations.

Spectrum is an FDA registered and inspected drug establishment. Our United States Food and Drug Administration (USFDA) Registration numbers are as follows:

Spectrum-Gardena, CA: 2020632
Spectrum-New Brunswick, NJ: 2246824
Spectrum -Shanghai, China: 3006174778

Thank you for your interest with Spectrum products. Please feel free to contact the Quality Assurance department at 310-516-8000 or via email at qualityassurance@spectrumchemical.com if we may be of further assistance.

Sincerely,

Michelle Weston

Quality Assurance Specialist

Michelle Weston



May 16, 2016

Certificate of cGMP

Dear Valued Customer:

Spectrum Chemicals and Laboratory Products certify that the following product(s) is produced, processed, packaged and held in compliance with current Good Manufacturing Practices (cGMP) in accordance with the applicable parts of 21 CFR, parts 210 and 211 of the Code of Federal Regulations.

Catalog Number	Product Name	
MI501	Light Mineral Oil, NF	

Spectrum is an FDA registered and inspected drug establishment. Our United States Food and Drug Administration (USFDA) Registration numbers are as follows:

Spectrum-Gardena, CA: 2020632
Spectrum-New Brunswick, NJ: 2246824
Spectrum-Shanghai, China: 3006174778

Thank you for your interest with Spectrum products. Please feel free to contact the Quality Assurance department at 310-516-8000 or via email at qualityassurance@spectrumchemical.com if we may be of further assistance.

Sincerely,

Michelle Weston

Quality Assurance Specialist

Michelle Wester



May 13, 2016

Re: Light Mineral Oil, NF-MI501

To Whom It May Concern:

Thank you for your interest in Spectrum high quality chemicals.

We at Spectrum Chemical Mfr. Corp. understand the concern regarding Bovine Spongiform Encephalopathy (BSE). Please be assured that the chemical

Light Mineral Oil, NF-MI501

is BSE/TSE free.

If you have any further questions, please contact Tech Services at (310) 516-8000 Extension 5471, or by email at techservices@spectrumchemical.com.

Sincerely,

Darlene Dagdag-Lyudmirskiy Technical Services Spectrum Chemical Mfr. Corp.

This document has been produced electronically and is valid without a signature



May 19, 2016

Re: Light Mineral Oil, NF- MI501

To Whom It May Concern:

Thank you for your interest in Spectrum high quality chemicals.

We at Spectrum Chemical Mfr. Corp. understand the concern regarding the presence of allergens in raw materials. Please be assured that the following chemical does not contain (Milk; Egg; Fish; Shellfish; Lupin; Tree nuts; Mollusks; Wheat; Peanuts; Soy; Cereals containing Gluten; Celery; Mustard; Sesame Seed).

Light Mineral Oil, NF- MI501

If you have any further questions, please contact Tech Services at (310) 516-8000 Extension 5471, or by email at techservices@spectrumchemical.com.

Sincerely,

Darlene Dagdag-Lyudmirskiy Technical Services Spectrum Chemical Mfr. Corp.

This document has been produced electronically and is valid without a signature



May 19, 2016

Re: Light Mineral Oil, NF- MI501

To Whom It May Concern:

Thank you for your interest in Spectrum high quality chemicals.

We at Spectrum Chemical Mfg. Corp. understand the concern regarding Aflatoxins in raw materials. To the best of our knowledge, the product listed below is not contaminated with Aflatoxins. Aflatoxins are not used in production. The following product does not come in contact with Aflatoxins at any stage of production.

Light Mineral Oil, NF- MI501

If you have any further questions, please contact Tech Services at (310) 516-8000 Extension 5471, or by email at techservices@spectrumchemical.com.

Sincerely,

Darlene Dagdag-Lyudmirskiy Technical Services Spectrum Chemical Mfr. Corp.

This document has been produced electronically and is valid without a signature



Label Information

The Spectrum label presents technical and safety information in an easily understood format. Our technical specialists stay abreast of the latest requirements of the Globally Harmonized System for Classification and Labelling of Chemicals (GHS), as well as the Occupational Safety and Health Administration (OSHA), the Food and Drug Administration (FDA) and other government regulatory agencies in order to ensure compliance, accuracy and concise hazard communication.



- A Bar Code
- GHS Hazard Pictograms
- Warning, Safety Data and Precautionary Information
- Product Catalog Number
- Item Name, Form, Grade
- Storage Color Band

- Size/Quantity
- Chemical Abstracts Service (CAS) Registry Number
- Caution Information
- DOT Shipping Information
- Toll-Free 24-Hour Chemical Emergency Telephone Number
- Empirical Formula, Formula Weight and Technical Specifications Panel
- Expiration Information
- Lot Number
- Kosher Certified by Kosher Supervision of America (KSA).

This color-coded band indicates the hazard most likely to be posed by that material under storage conditions. The criteria used to assign band colors have been established by the Storage Code working group of the Society for Chemical Hazard Communication (SCHC). It is recommended that like colors be stored together, unless otherwise stated, based on the color codes indicated to the right. However, it is the responsibility of the customer to check with their local fire department for possible conflicts with our recommendations when storing hazardous chemicals.

YELLOW: Oxidizer RED: Flammable GREEN: General Storage BLUE: Health Hazard

WHITE: Corrosive

Spectrum Chemical Mfg Corp

Corporate Headquarters:
769 Jersey Ave.
New Brunswick, NJ 08901

West Coast Facility: 14422 S. San Pedro St. Gardena, CA 90248 310.516.8000

732.214.1300



Certificate Of Analysis

Item Number	MI501	Lot Number	1FE0360
Item	Light Mineral Oil, NF		
CAS Number	8042-47-5		
Molecular Formula		Molecular Weight	

Test	Specification		Result
	min	max	
SPECIFIC GRAVITY @ 25°C	0.818	0.880	0.846
VISCOSITY @40.0 C	3.0	34.4 mm ² /s	12.28 mm ² /s
ACIDITY	TO PASS TEST		PASSES TEST
READILY CARBONIZABLE SUBSTANCES	TO PASS TEST		PASSES TEST
POLYCYCLIC AROMATIC HYDROCARBONS	TO PASS TEST		PASSES TEST
SOLID PARAFFIN	TO PASS TEST		PASSES TEST
IDENTIFICATION	TO PASS TEST		PASSES TEST
RESIDUAL SOLVENTS	TO PASS TEST		NO RESIDUAL SOLVENTS USED
SULFUR COMPOUNDS	TO PASS TEST		PASSES TEST
EXPIRATION DATE			03-FEB-2019
MANUFACTURE DATE			03-FEB-2016
APPEARANCE			CLEAR COLORLESS OILY LIQUID

Spectrum Chemical Mfg Corp 14422 South San Pedro Street Gardena 90248 CA



Certificate of Analysis Results Certified By:

Adan Hernandez

Quality Control Manager

Spectrum Chemicals & Laboratory Products

All pharmaceutical ingredients are tested using current edition of applicable pharmacopeia.



Certificate Of Analysis

Item Number	MI501	Lot Number	2FD0330
Item	Light Mineral Oil, NF		
CAS Number	8042-47-5		
Molecular Formula		Molecular Weight	

Test	Speci	Specification	
	min	max	
SPECIFIC GRAVITY @ 25°C	0.818	0.880	0.846
VISCOSITY @40.0 C	3.0	34.4 mm ² /s	12.95 mm ² /s
ACIDITY	TO PASS TEST		PASSES TEST
READILY CARBONIZABLE SUBSTANCES	TO PASS TEST		PASSES TEST
POLYCYCLIC AROMATIC HYDROCARBONS	TO PASS TEST		PASSES TEST
SOLID PARAFFIN	TO PASS TEST		PASSES TEST
IDENTIFICATION	TO PASS TEST		PASSES TEST
RESIDUAL SOLVENTS	TO PASS TEST		NO RESIDUAL SOLVENTS USED
SULFUR COMPOUNDS	TO PASS TEST		PASSES TEST
EXPIRATION DATE			18-MAR-2019
DATE OF MANUFACTURE			18-MAR-2016
APPEARANCE			COLORLESS OILY LIQUID

Spectrum Chemical Mfg Corp 755 Jersey Avenue New Brunswick 08901 NJ



Certificate of Analysis Results Certified By:

Mulbah F. Dwanah Laboratory Supervisor

Spectrum Chemicals & Laboratory Products

All pharmaceutical ingredients are tested using current edition of applicable pharmacopeia.



January 26, 2016

RE: Lot Numbering System

Dear Valued Customer:

This letter is to inform you of Spectrum Chemicals and Laboratory Products' Lot Numbering System. The system is based on an alpha-numerical sequence which provides the month, year and location of production.

The lot numbering system utilized until 2010 is a sequence of **six characters**, two letters followed by four numbers. The first letter represents the year, for example, Y denotes 2009 and Z denotes 2010. The second letter represents the month and site, for example, A-L denotes January through December at Spectrum's Gardena, CA facility, while M-X denotes January through December at the New Brunswick, NJ facility. The following four numbers are sequentially assigned.

Example: Zl0928 = The 928th material produced in California in September 2010

The lot numbering system utilized for 2011 and forward, is a sequence of **seven characters**. The first character, a number, represents the production facility:

1 = Gardena, CA Facility

2 = New Brunswick, NJ Facility

3 = China Facility

The second character, a letter, represents the year. For example, A denotes 2011 and B denotes 2012. The third character, a letter, represents the month, with A denoting January and L denoting December. The following four numbers are sequentially assigned.

Example: 2AA0706 = The 706th material produced in New Jersey in January 2011

Thank you for your interest with Spectrum products. Please feel free to contact us at 310-516-8000 or via email at qualityassurance@spectrumchemical.com if we may be of further assistance.

Sincerely,

Michael Dang

Manager, GMP Compliance



Stability – Shelf Life Guidance

Product Covered: MI501, Light Mineral Oil, NF

Spectrum Chemical's manufacturing partner has assigned the following shelf life guidance for the product listed above.

The product, MI501, Light Mineral Oil, NF, is assigned a 36 months shelf life from date of manufacturing. The quality and integrity of the chemical depends on the handling and storage conditions. Please refer to the Safety Data Sheet for proper storage and handling procedures.

Adan R. Hernandez Quality Control Manager

Corporate Headquarters 769 Jersey Avenue New Brunswick, NJ 08901-3605